



K 760 with OilGuard

OVERVIEW

FEATURES

SPECIFICATIONS

PARTS & ACCESSORIES





MEDIA

FIND A DEALER

## Power Cutters

# Husqvarna K 760 with OilGuard

Ever had engine trouble caused by the wrong oil-fuel mix or oil type? Our unique OilGuard technology will help you prevent the damage from this. An optical detection system guards your machine, and reduces the revs per minute if something is wrong, saving you maintenance costs. Perfect for the rental industry.

 Cylinder displacement	<b>4.48 cu.inch</b>
 Cylinder displacement	<b>73.5 cm<sup>3</sup></b>
 Blade diameter, max	<b>14 in</b>
 Blade diameter, max	<b>350 mm</b>

Add to wish list



Find a dealer near you



Manuals

### Engine

Cylinder displacement	<b>73.5 cm<sup>3</sup></b>
Cylinder bore	<b>51 mm</b>
Cylinder stroke	<b>36 mm</b>
Maximum power speed	<b>9000 rpm</b>
Max engine/motor RPM	<b>9300 rpm</b>
Idling speed	<b>2700 rpm</b>
Output shaft RPM, max	<b>4700 rpm</b>
Fuel consumption	<b>470 g/kWh</b>
Fuel tank volume	<b>0.9 l</b>
Electrode gap	<b>0.5 mm</b>
Spark plug	<b>NGK BPMR7A</b>
Engine cooling	<b>Fan/Air</b>
Lubricant type	<b>Husqvarna 2 stroke or equiv. at 50:1</b>

### Equipment

Arbor diameter	<b>20/25,4 mm</b>
Blade diameter, max	<b>350 mm</b>
Cutting depth, max	<b>125 mm</b>
Peripheral speed, max	<b>90 m/s</b>

### Sound and Noise

Sound pressure level at operators ear	<b>101 dB(A)</b>
Sound power level, guaranteed (LWA)	<b>115 dB(A)</b>