






WS 463

[Overview](#) [Features](#) [Specifications](#) [Accessories](#) [Where To Buy](#)

Wall saws

Husqvarna WS 463

WS 463 hydraulic wall saw is very powerful and is designed to make your work more efficient. Use it to cut reinforced concrete, brick and other building materials, up to 730 mm thickness. It can be used for all kinds of openings and sawing including stair, bevel and flush cutting.

-  Blade diameter, min **600 mm**
-  Blade diameter, max **1600 mm**
-  Cutting depth, max **730 mm**

Article number: WALL SAW WS 463 1000 mm | 25.4/6 mm - 965 15 60-02

[Get quote](#) >

Our local salesman can give you **price quotes**, **book a demo** or **give you a call** to talk more.

[Add to wish list](#) >

[Spare parts](#) | [Manuals](#)



Motor

Output shaft RPM, max	14000 rpm
Max spindle torque	350/200/120

Hydraulics

Hydraulic oil flow	65 l/min
Hydraulic pressure, max	230 bar

Dimensions

Weight saw carriage	22 kg
Weight saw unit	22 kg

Other

Water pressure, max	7 bar
---------------------	-------

Cutting equipment

Arbor diameter	25.4/60 mm
Blade diameter, max	1600 mm
Blade diameter, min	600 mm
Cutting depth, max	730 mm
Starter blade diameter, max	1000 mm

Transmission

Number of gearbox speeds	3
--------------------------	---

Sound and noise

Sound power level, measured	117.8 dB(A)
Sound pressure level at operators ear	100.3 dB(A)