

Husqvarna®

WS 440 HF

[Overview](#) [Features](#) [Specifications](#) [Accessories](#) [Where To Buy](#)

WS 440 HF electric wall saw gives you increased possibilities for fast and efficient cutting in reinforced concrete, brick and other building materials, up to 21 in. thickness. Use this wall saw for all kinds of openings and sawing including stair, bevel and flush cutting. The user-friendly ergonomic design and ease of transport make your job fast and efficient. WS 440 HF can be combined with CS 10, transforming it into a perfect wire saw.

- Blade diameter, min **600 mm**
- Blade diameter, max **1200 mm**
- Cutting depth, max **530 mm**

Article number: WALL SAW WS 440 HF 800 mm - 967 64 66-02

\$55,014.00

Get quote

Add to wish list

[Spare parts](#) | [Manuals](#)

Our local salesman can give you **price quotes**, **book a demo** or **give you a call** to talk more.



Motor

Output shaft RPM, max
Max spindle torque
Spindle starting torque, Nm

1200 rpm
125 Nm
100 Nm

Transmission

Number of gearbox speeds

1

Sound and noise

Sound power level, guaranteed (LWA)
Sound power level, measured

109 dB(A)
108 dB(A)

Cutting equipment

Arbor diameter
Blade diameter, max
Blade diameter, min
Cutting depth, max
Starter blade diameter, max

25,4/60 mm
1200 mm
600 mm
530 mm
1000 mm

Dimensions

Product size length
Product size width
Product size height
Weight
Weight saw carriage
Weight saw unit

2200 mm
900 mm
800 mm
25 kg
3.9 kg
25 kg

Other

Water flow, min
Water pressure, max
Water temp at min flow, max

3.5 l/min
7 bar
25 °C