

Husqvarna®

WS 482 HF

[Overview](#) [Features](#) [Specifications](#) [Accessories](#) [Media](#) [Where To Buy](#)

WS 482 HF is a very powerful wall saw for cutting reinforced concrete, brick and other building materials, up to 29 in. thickness. The water-cooled electric motor has an unbeatable power-to-weight ratio. This wall saw can be used for all kinds of openings and sawing including stair, bevel and flush cutting. It's easy to assemble, run and transport making your job more comfortable and faster. WS 482 HF can be combined with CS 10, transforming it into a perfect wire saw.

- Blade diameter, min **600 mm**
- Blade diameter, max **1600 mm**
- Cutting depth, max **730 mm**

Article number : WALL SAW WS 482 HF 800 mm - 967 64 67-02

\$75,771.00

Get quote

Add to wish list

[Spare parts](#) | [Manuals](#)

Our local salesman can give you **price quotes**, **book a demo** or **give you a call** to talk more.



Motor

Output shaft RPM, max	1200 rpm
Max spindle torque	235/174 Nm
Spindle starting torque, Nm	200/150 Nm

Transmission

Number of gearbox speeds	2
--------------------------	----------

Sound and noise

Sound power level, guaranteed (LWA)	109 dB(A)
Sound power level, measured	108 dB(A)

Cutting equipment

Arbor diameter	25.4/60 mm
Blade diameter, max	1600 mm
Blade diameter, min	600 mm
Cutting depth, max	730 mm
Starter blade diameter, max	1000 mm

Dimensions

Product size length	2200 mm
Product size width	900 mm
Product size height	800 mm
Weight	28 kg
Weight saw carriage	3.9 kg
Weight saw unit	29.6 kg

Other

Water flow, min	3.5 l/min
Water pressure, max	7 bar
Water temp at min flow, max	25 °C