



CS 10

[Overview](#) [Features](#) [Specifications](#) [Accessories](#) [Media](#) [Where To Buy](#)

The CS 10 is a very useful and efficient saw system, thanks to a number of smart solutions. The saw is coupled to our electric wall saws WS 482 HF or WS 440 HF. It can be mounted on both sides of the track, and the wire's direction of rotation is reversible. You can saw both vertically and horizontally. Plus there's no need for water for dry cuts in cases when slurry is a concern.

- Net wire storage capacity **10 m**
- Output power with WS 440 HF and PP 440 HF **13 kW**
- Output power with WS 482 HF and PP 480 HF **19 kW**
- Weight with WS 440 HF **135 kg**

Article number: WIRE SAW CS 10 EU/US/RoW | Swivel pulleys - 966 56 57-01

[Get quote](#) >

[Add to wish list](#) >

[Spare parts](#) | [Manuals](#)

Our local salesman can give you **price quotes, book a demo or give you a call** to talk more.



Engine

Motor for wire drive
 Output power with WS 440 HF and PP 440 HF
 Output power with WS 482 HF and PP 480 HF
 Output power with WS 482 HF and PP 490
 Spindle starting torque, Nm

Electric Wall Saw
13 kW
19 kW
25 kW
160 Nm

Sound and noise

Sound power level, guaranteed (LWA)
 Sound power level, measured
 Sound pressure level at operators ear

100 dB(A)
99 dB(A)
86 dB(A)

Dimensions

Weight **100 kg**
 Weight with WS 440 HF **135 kg**
 Weight with WS 482 HF **138 kg**

Other

Direction of rotation **Both directions**
 Wire configuration in drive unit, min **1 m**
 Net wire storage capacity **10 m**