

KS 216 M Lasercut (619216000) Mitre Saw (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 619216000 EAN 4007430256539



Product may differ from Image



- Compact light weight, suitable also for one-handed transport
- Robust die-cast aluminium design for the highest demands
- Easy transport thanks to ergonomically-designed handles and saw head lock
- Effective dust extraction via integrated dust scoop
- Fast and precise setting of common angles using stop points
- Laser for exact display of the cutting line (mains powered, no batteries required)
- Adjustable and extendable table width extension, removable to put long panels, slabs etc. underneath
- Bright LED work light for illumination of the cutting line (mains powered, no batteries required)
- Sliding high rear fence profiles for safe sawing
- Material clamp for secure fixing of the work piece from the top or front
- Saw head can be inclined to the left, with additional angle range for undercuts
- All scales and operating elements are visible from the working position and can be operated intuitively
- Easy saw blade change by means of spindle lock: No dismantling of the pendulum protective cover required



Technical data

Characteristics

Dimensions	475 x 465 x 285 mm / 1.6 x 1.6 x 1 ft mm
Maximum cutting width 90°/45°	120 / 80 mm // 4 11/16 / 3 1/8 " mm
Maximum cutting depth at 90°/45°	60 / 45 mm // 2 3/8 / 1 3/4 " mm
Cutting capacity 90°/90°	120 x 60 mm / 4 11/16 x 2 3/8 " mm
Cutting capacity 45°/45°	80 x 45 mm / 3 5/32 x 1 3/4 " mm
Turntable setting left/right	47 / 47 °
Saw blade tilt left/right	47 / 2 °
Saw blade	216 x 30 mm / 8 1/2 x 1.181 " mm
Rated input power S1 100%	1100 W
Rated input power S6 20%	1350 W
No-load speed	5000 /min
Revolutions at rated load	3450 /min
Cutting speed	57 m/s / 187 ft/s m/s
Weight	9.4 kg / 20.7 lbs kg
Cable length	2 m / 7 ft m
Noise emission	N OF
Sound pressure level	93 dB(A)
Sound power level (LwA)	100 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide saw blade (40 teeth)
Material clamp
Tool for saw blade change
Chip collection bags
2 Table length extensions
Length guide