

KS 305 M (619003000) Mitre Saw

Cardboard box

Order no. 619003000
EAN 4007430299727



Product may differ from Image



- Highest precision from direct saw head mount.
- Compact light weight, suitable also for one-handed transport
- Robust die-cast aluminium design for the highest demands
- Easy transport thanks to ergonomically-designed handles and saw head lock
- Fast and precise setting of common angles using stop points
- Laser for exact display of the cutting line (mains powered, no batteries required)
- Adjustable and extendable table width extension, removable to put long panels, slabs etc. underneath
- Bright LED work light for illumination of the cutting line (mains powered, no batteries required)
- Sliding high rear fence profiles for safe sawing
- Material clamp for secure fixing of the work piece from the top or front
- Saw head can be inclined to the left, with additional angle range for undercuts
- All scales and operating elements are visible from the working position and can be operated intuitively
- Easy saw blade change by means of spindle lock: No dismantling of the pendulum protective cover required

Technical data
Characteristics

Dimensions	600 x 600 x 600 mm / 23 5/8 x 23 5/8 x 23 5/8 " mm
Maximum cutting width 90°/45°	200 / 140 mm
Maximum cutting depth at 90°/45°	102 / 60 mm
Cutting capacity 90°/90°	200 x 80 mm
Cutting capacity 45°/45°	130 x 45 mm
Turntable setting left/right	52 / 52 °
Saw blade tilt left/right	47 / 2 °
Saw blade	305 x 30 mm
Rated input power S1 100%	1600 W
Rated input power S6 20%	2000 W
No-load speed	3700 /min
Revolutions at rated load	2600 /min
Cutting speed	60 m/s
Weight	17 kg

Noise emission

Sound pressure level	97 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide saw blade (56 teeth)
 Additional fence
 Material clamp
 Tool for saw blade change
 Cable Winder
 Chip collection bags
 2 Table length extensions
 Length guide

Ташев-Галвинг ООД
 www.tashevgalving.com