

CM42 COMPACT

FEATURES

- Wide conveyor cart, long reinforced frame
- Ergonomic handle
- Folding legs with repositionable tightening handle & transport wheels
- Wide conveyor cart with tilted wheels, anti-pivoting and locking system
- High accuracy cutting guide with per-degree angular setting

BENEFITS

- Can cut a 60x60cm slab in two 30cm halves.
- Better comfort during use
- Easy transportation and storage.
- Better stability and durability
- Quick, precise and easy cut without additional accessory



PRODUCT DATA

Item No.	701846 47620	Supply Voltage/ Power kW	230V 1~ / 2,2kW (3 Hp)	Tilting table	Optional
EAN 13 Code	5450248 563617	Fuse/Generator	16A / 6 kVA	Max. cutting depth (mm)	135mm
		Blade x bore (mm)	Ø 400 x 25,4	Max. cutting length (mm)	780
		Tool speed RPM	2800 min ⁻¹	Max. material height (mm)	200
		Dimensions (LxWxH) (mm)	1187 x 620 x 1360	Table size (mm)	500 x 540
		Dimensions (folded legs) (mm)	1187 x 620 x 740	Hand Arm Vibrations	< 2,5 m/s ²
		Weight	90kg	Sound power / pressure level	92 dB (A) / 80 dB (A)



3HP



2,2kW



230V

PRODUCT FEATURES



MAX CUT DEPTH



FOLDING FEET



ADJUSTABLE CUTTING-DEPTH HANDLE



ANTI PIVOTING SYSTEM

DIAMOND BLADE RECOMMENDATIONS FOR CM42

Substrate / Material	BETON	SILENCIO	UNIVERSAL	ALL MATERIALS
Recommended Product	PRO BETON	EXTREME UNI SILENCIO	EXTREME UNIVERSAL	PRO 4X4 EXPLORER
Diameter x bore (mm)	400 x 25,4	400 x 25,4	400 x 25,4	400 x 25,4
Item No.	701846 27062	701846 40270	701846 11438	701846 02095
Page reference	20	27	26	36