

DIAMANT DR-350



For ceramic tiles and all types of building materials such as brick, facebrick, fire brick, etc.
 With thermal and overload protection devices.
 Water pump refrigeration of blade (with flow control valve).
 Diamond Blade Ø 12" (300 mm.) - 14" (350 mm.) not included.
 Vertically mobile head with plunge cut capability and foldable head for miter cuts.
 Electric cable: 4.9 ft. (1,5 m.)
 With guide to allow repetitive cuts.
 Large sliding table 22 7/8" x 20 2/3" (58 x 52 cm.) mounted on sealed bearings.
 Direct drive.



DIAMANT	REF.														
DR-300-EN 230V 50Hz.	56940	1	**1	230V-50 Hz.	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes
DIAMANT DR-300-EN 220V 60Hz.	56942	1	**1	220V-60 Hz.	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes
DIAMANT DR-300-EN 120V 50Hz. UK	56944	1	**1	120V-50 Hz.UK	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes
DIAMANT DR-300-EN 120V 60Hz. USA	56945	1	**1	120V-60 Hz.USA	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes
DIAMANT DR-300-EN 230V 50Hz. 3F	56946	1	**1	230V-50 Hz.	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes
DIAMANT DR-300-EN 380V 50Hz. 3F	56948	1	**1	380V-50 Hz.	2800	69 cm	44x44 cm	∞ cm	92/130 mm	No	300-350 mm	115x69x132,5 cm	63,5 kg	93 kg	Yes

