Е Технически характеристики

Машина Rubi за рязане на строителни материали циркулярна с водеща греда 1500 W, ф 250 мм, 1550 мм, DCX-250 Xpert



**REAL CUT (without plunge effect)

	REF	5	RPM			$\langle \rangle$, 111112	\odot	(ret)		<u></u>	Щ	Ċ
DCX-250 XPERT 1250	52960 52929 52961 52962	230V/50Hz 220V/60Hz 110V/50Hz 120V/60Hz	2750 3350 2750 3350	2 HP (1.5kW)	**125 cm 49 3/16" ^[direct] 133 cm 52 in	88.5 x 88.5 cm 35 x 35 in 110 x 110 cm 43.3 x 43.3 in	60 - 90 mm 2 3/8 / 3 9/16"		250 mm 10"	16mm 5/8 ^(USA) 25.4 mm 1"	1920 x 740 x 1300 mm 75.5 x 29 x 51 in	- 1	1 -	78 kg 172 Lb
DCX-250 XPERT 1550	52970 52937 52971 52972	230V/50Hz 220V/60Hz 110V/50Hz 120V/60Hz	2750 3350 2750 3350		**155 cm 61 1/16" ^[direct] 163 cm 64 in						2220 x 740 x 1300 mm 87.4 x 29 x 51 in			86 kg 189.5 Lb

Description

RUBI's DCX-250 Xpert range of professional cutters are designed for the intensive cutting of porcelain stoneware tiles (BIa), and any other type of tile (BIIa / BIIb / BIII / AIb), while allowing the occasional cutting of natural stone.

The design of the DCX-250 Xpert cutters includes a highly reinforced aluminum chassis with an innovative triple beam system and steel fronts to improve the stability and rigidity of the entire chassis.

The moving head of the DCX-250 Xpert is supported by a reinforced guide, also made of aluminum, for a better and precise finish in the cut. This system also incorporates a high-performance plunge effect, allowing the cutting height to be adjusted to the user's needs.

RUBI's DCX-250 Xpert electric cutters include the C3 Python cooling system that allows the water application point to be adjusted according to the thickness of the material, ensuring that the water hits the cut point directly. The C3 Python system allows to increase the efficiency of the cooling system and reduces the dispersion and loss of water. More efficient cooling helps increase the performance of the diamond blade.

The cooling system of the DCX-250 Xpert is completed with a double steel decanter for a more efficient recovery of the used water, directed towards the external 30-litre water tank. By using an external tank, handling it in cleaning and filling operations is easier and faster.

The models of the DCX-250 Xpert range incorporate reinforced handles and wheels (off-road type), which provide a better experience in transporting and handling the cutters. Its folding and reinforced legs include a quick locking system and a safety device that prevents involuntary folding during work. In addition, the DCX

includes an adjuster that guarantees a correct leveling of the cutting table.

Always thinking about the safety of the professional, RUBI equips the DCX-250 Xpert models with its ZERO DUST system, patented and certified by the TNO *, which allows, thanks to the reduction of respirable dust particles that are generated during cutting, safe exposure to %silica from ceramic materials and natural stones.

* offers "safe exposure" values to respirable quartz dust particles within the "user's inhalation zone", which allows RUBI electric cutters to work up to 3 hours a day * and consecutive cutting ceramic tile and 1 hour in cutting natural stone in a closed and unventilated space of 15 m3.





Продукт: Машина Rubi за рязане на строителни материали циркулярна с водеща греда 1500 W, ф 250 мм, 1550 мм, DCX-250 Xpert

Категория: <u>Машини за рязане на строителни материали с водеща греда</u> Бранд: Rubi

Категория бранд: Машина Rubi