

# MASONRY SAW TBE350★★

CUTTING DEPTHS UP TO 110 MM



Swivelling saw head allows 45° mitre cuts to be made



Two robust castors provide optimum manoeuvrability at the deployment location



Included angle stop for cuts from 30° to 90°

- Uncompromising price/performance ratio
- Clean cutting thanks to solid saw table with non-slip surface
- Mitre cuts are child's play to make using the swivelling saw head
- Continuous tool cooling and minimal amount of service work due to water pump location that prevents soiling
- Problem-free transport thanks to removable table feet
- Maximum safety due to centrally located emergency stop switch
- High flexibility due to many adjusting and usage options

**TYROLIT**

Ташев Галвинг ООД  
[www.tashev-galving.com](http://www.tashev-galving.com)

## Technical data

SAW BLADE	
Max. cutting depth	110 mm
Max. saw blade Ø	350 mm
Cutting length	600 mm
Saw blade speed	2,800 rpm
Saw blade holder Ø	25.4 mm

DRIVE	
Drive/motor	Electric
Output	2.2 kW
Standard voltage/frequency	230 V / 50 Hz
Optional voltage/frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

DESIGN	
Infinitely adjustable cutting depths	
Angle cutting function (angle stop)	
Mitre cutting function (swivelling saw head)	
Cap cutting function	
Water tank made from powder-coated steel	
Electric water pump	
Dismantlable	

DIMENSIONS & WEIGHT	
Length	1,140 mm
Width	640 mm
Height	1,230 mm
Weight	79 kg

## System

MASONRY SAW TBE350**		
10981423	Masonry saw TBE350S / 230 V	
10981424	Masonry saw TBE350S / 110 V	