

# Технически характеристики

## **PS ULTRA**

The PS Ultra is a compact, slim-line spray sprinkler with the option of pre-installed nozzles for faster installation.

#### **KEY BENEFITS**

- Enhanced cap for more durability, easier handling, and extended riser seal life
- · Large inlet filter screen for increased debris resistance
- Check valve option eliminates low-head drainage
- Heavy-duty spring for consistent riser retraction

#### **ADDITIONAL FEATURES**

- Directional flush plug design for cleaner installation
- Two-piece ratcheting riser
- 5 cm and 10 cm models can retrofit into older style PS models
- · Compatible with all female-threaded nozzles

#### **OPERATING SPECIFICATIONS**

- Operational pressure range: 1.4 to 4.8 bar; 140 to 480 kPa
- Warranty period: 2 years

#### **FACTORY-INSTALLED OPTIONS**

- Flush plug (large filter screen not included)
- Nozzles 2.4 m, 3.0 m, 3.7 m, 4.6 m, 5.2 m, 1.5 x 9.0 m side strip
- Large inlet filter screen included in 10 cm and 15 cm pre-installed nozzle models

#### **USER-INSTALLED OPTIONS**

- ww.tashev-gali • Check valve installs in filter screen for 10 cm and 15 cm models (up to 2 m of elevation; P/N 462237SP)
- Large inlet filter screen (P/N 162900SP)
- Shutoff nozzle (P/N 916400SP)



#### PSU-02

Retracted height: 12 cm Pop-up height: 5 cm Exposed diameter: 3 cm Inlet size: 1/2"



Retracted height: 18 cm Pop-up height: 10 cm Exposed diameter: 3 cm Inlet size: 1/2"



#### Examples:

PSU-04 - 15A = 10 cm pop-up, with a 4.6 m adjustable nozzle **PSU-02 - 5SS** = 5 cm pop-up, with a 1.5 m x 9.0 m side stripPSU-06 - 10A = 15 cm pop-up, with a 3.0 m adjustable nozzle

PSU-04 - 12A - NFO = 10 cm pop-up, with a 3.7 m adjustable nozzle, nozzle filter only



### PSU-06

Retracted height: 24 cm Pop-up height: 15 cm Exposed diameter: 3 cm Inlet size: 1/2"