







PHARMA 30 - INDUSTRIAL THREE PHASE



CHEMICAL-PHARMACEUTICAL











- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Integrated filter cleaning system
- ✓ Complete steel construction
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Low noise level
- ✓ Compact and mobile
- ✓ High filtration efficiency
- ✓ Accessory kit as standard

SUCTION UNIT		
Voltage	V - Hz	400 - 50
Power	kW	2,2
Electrical protection	IP	55
Max waterlift	mmH2O	2.600/1.900
Max air flow	m³/h	318
Suction inlet	mm	50
Noise Jevel (EN ISO 3744)	dB(A)	67
FILTER UNIT		
Filter Type		Cartridge
Surface - Diameter	cm²-mm	30.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE
Air load on filter	m³/m²/h	106
Cleaning system		Dustop
COLLECTION UNIT		
Discharge system		Roll-out container
Capacity	lt.	33

cm

VOLUME

Dimensions

Weight

52x69x147h

75





SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

The polyester cartridge filter placed inside the filter chamber guarantees a large filter

COLLECTION UNIT

The detachable steel collection tank has a quick release system for the rapid disposal of the aucked material.





OPTIONALS

- ABSOLUTE HEPA FILTER
- ANTISTATIC FILTER CLASS M
- STAINLESS STEEL COLLECTION TANK
- STAINLESS STEEL TANK AND FILTER CHAMBER
- TOTAL STAINLESS STEEL CONSTRUCTION
- ✓ ATEX CERTIFICATION
- ✓ INTERNAL POLISHING FOR FILTER CHAMBER AND TANK