

# MIXERS RUBIMIX-7





#### Use:

• For mixing cement base adhesives, resins, paints and other materials.

## Characteristics:

- Two-handled mixer.
- Power: 1200W
- Geared motor 1 speed.
- Double insulation.
- Electronic speed control:
  - 0 760 RPM
- M14 thread connection for direct coupling of the mixing paddle.
- Ø maximum paddle; 140 mm.
- Includes:
  - M-120-R type mixing paddle for cement based adhesives.
  - Set of wrenches.
  - Set of replacement brushes.
- Available on 110/130V and 210/240V 50/60Hz

## Packaging:

- Full color carton box on consolidated carton box with RUBI flexography, on European standard pallet.
- Consolidated box dimensions: 66x40x26 cm.
- 2 units per consolidated box.
- 24 units per pallet.

### Norma

• Conforms the Regulations of Machines; 98/37/EC, EN 640745-1:2006, EN 60745-2-1/A11:2007

MODELS							
	REF.	٧	W	R.P.M	Mixing capacity	Ø Máx. Paddle	Kg.
RUBIMIX-7	26900	230-50/60	1200	0-760	<b>4</b> 0 l.	140 mm.	
RUBIMIX-7 UK	26901	110-50/60					3.250 Kg
RUBIMIX-7 UK	26902	230-50/60					
RUBIMIX-7 USA	26902	120-50/60					

All deb., information and recommendations contained in this product sheet, referred to products, vay of use and applications, are based on actual knowledge.
Specific reast may be subject to variation, since fill outside voir control facilities con officions flictly to be recountered in the use and application.
Is the customer's reportable; to setter, drough their own ritis and restring each product scales the purpose to which goes and if the actual conditions of
Is the customer's reportable; to setter, drough their own ritis and restring each product scales to the purpose to which goes and if the actual conditions of