

## RUBIMIX-9 SUPERTORQUE



Facilitates homogeneous mixing of the materials and prevents the creation of bubbles and/or lumps.



- 1 Electric mixer with high torque.
- 2 Progressive switch (rpm control) to OPTIMISE the mixing of each material.
- 3 Equipped with a mechanical 2 SPEED gearbox (450/780 rpm).
- 4 Better electrical SAFETY thanks to its double insulation.

- ATTRACTIVE and FUNCTIONAL Design.
- Connection to mixing paddles with M14 thread.
- Double handle with bi-material grip providing better ERGONOMICS, COMFORT and STABILITY.
- Chassis in TECHNICAL, LIGHT, and STRONG plastic. Maximum RELIABILITY AND DURABILITY.
- SAFETY on button. Prevents unintentional start-up.
- Smooth start system.
- Direct access to the motor's brush housing for quick and easy maintenance.
- Includes mixing paddle with 3 helixes of 140 mm diameter for mortars and cementitious adhesives.
- Option to couple a RUBI FAST-IN adapter for paddles (NOT included).
- Includes brushes and 19 and 22 mm spanners.
- Version available with transport case (ref. 26974).
- Compatible with chucks and range of mixing paddles RUBI.

### Accessories

Mortar Mixer 3 ZN-Zinc plated HELIX

Mortar Mixer M14 Thread 3 ZN-Zinc plated HELIX

Mortar mixer paddle Thread M14 3HELIX

RUBIMIX buckets

	REF	W	RPM			
RUBIMIX-9 SUPERTORQUE	26970	1800 W 230V-50/60Hz. 1° 0-650 / 2° 0-850	11.2 Lb 5.1 kg	2	18	
RUBIMIX-9 SUPERTORQUE UK	26971	1800 W 110V-50/60Hz. 1° 0-650 / 2° 0-850	11.2 Lb 5.1 kg	2	18	
RUBIMIX-9 SUPERTORQUE UK	26972	1800 W 220V-50/60Hz. 1° 0-650 / 2° 0-850	11.2 Lb 5.1 kg	2	18	
RUBIMIX-9 SUPERTORQUE USA + CHUCK	26973	1800 W 120V-50/60Hz. 1° 0-650 / 2° 0-850	11.2 Lb 5.1 kg	2	18	
RUBIMIX-9 SUPERTORQUE + CASE	26974	1800 W 230V-50/60Hz. 1° 0-650 / 2° 0-850	19.51 Lb 8.85 kg	2	18	
RUBIMIX-9 SUPERTORQUE + CHUCK	26975	1800 W 230V-50/60Hz. 1° 0-650 / 2° 0-850	11.2 Lb 5.1 kg	2	18	

